



DFIT172-71A-K-PP

7.000 - 11.000 l/h

Typical applications
Plating and process industry



- Features**
- Environmentally safe in-tank installation
 - Compact filter system
 - Sealless pump, can run dry
 - Self priming

- Options**
- Customised mounting plate
 - Suction extension pipe
 - CPVC/PVDF sockets or Hose connection
 - Bag filters
 - SS filter systems
 - Out-of-tank mounting




DF172-71A-K-PP


Filter systems series DF170 - PP/PVDF




Qmax l/h	Hmax m	Motor kW	Immersion length (mm)	Mounting plate (mm)	Connection outlet	Pump	Chamber	Medium	Material
8000	12	0,55	400	600 x 300	d32/DN25	DF(IT)172	71A/72A	K/P	PP/PVDF
						DF(IT)172	7A	B1	PP
11000	17	0,75				DF(IT)173	71A/72A	K/P	PP/PVDF
						DF(IT)173	7A	B2	PP

 www.hendor.com

K = cartridges
 Qty x L
 71A-K = 7 x 10"
 72A-K = 7 x 20"

P = discs
 Qty OD/ID
 31Z-P = 32 x 136/32
 71Z-P = 32 x 205/32

B = bag
 L x OD (mm)
 B1 = 430 x 180
 B2 = 860 x 180