



MX60-7A-B2-FM-PP

1.000 - 22.000 l/h Bag

Typical applications

Plating and process industry

Features

Bag Filtration

- Large dirt holding capacity
- Easy bag change
- Low operating cost

Bag Filtration Plus

- Bag with PP micro fibres
- Oil / grease
- Gel like sludge

Carbon purification

- Efficient removal of organic impurities

Options

- Hose connection
- Viton
- Buna / NBR
- Multiple bag chambers for larger volumes
- Stainless Steel bag filter systems



MX60-7A-B1-PP

Multi purpose bag filter systems

i www.hendor.com

Pump	l/h	kW	Union (d/DN) In Out	Hose In Out	Type	Chamber	Flow Control	Material
Magnetic drive	2000	0,18*	32/25 25/20	1 1/4" 1"	M11	7A-B1 7A-B2	FM FF	PP-EPDM
	4000	0,18*			MX40			
	6000	0,25*	32/25 32/25	1 1/4" 1 1/4"	MX60			
	8000	0,37*			MX90			
	10000	0,55	40/32 32/25	1 1/2" 1 1/4"	MX120			
	14000	0,75			MX160			
	18000	1,10	40/32 40/32	1 1/2" 1 1/2"	MX210			
	22000	1,50	50/40 40/32	2" 1 1/2"	MX260			

Selection: MX60 7A-B2 FM PP

L x OD (mm)
7A-B1 = 430 x 180
7A-B2 = 860 x 180

