

Output power:	max. 132 kW	Typical applications:	
DC current:	up to 7200 A (max. 7200 A / 18 V)	Chrome plating	Barrel plating
DC voltage:	up to 1000 V (max. 1000 V / 130 A)	Anodizing/Aluminium colouring	Rack plating

Water cooled DC power supply in switch mode technology, designed for the direct installation at the electroplating tank with minimized floor space.



POWER STATION pe5710-W, front view - example

Standard plinth: on picture above: 200mm
optional: plinth 100mm

EMV: EN50011 class A, group B ; EN61000-6-4 and EN61000-6-2;
CE-conformity low voltage guide line: EN50178

Extendable power range

The power range can be extended by wiring the DC outputs of several cabinets in parallel (sum current) or in serial (sum voltage)

Characteristic values

Linearity inaccuracy:

- for amperage < 1 %
- for voltage < 0.5 % (depending on regulation mode)

Ripple less than < 1 % RMS

Efficiency typical > 90 %

Powerfactor 0,95

Constant current and voltage control (optional: power regulation)

Inrush current protection

Over temperature protection

Pulse operation optional

Mains supply: standard 3 x 400 V +/- 10 % / 50-60 Hz
(other voltages on request)

Cooling

Water cooled / cooling water specification: see page 2

Ambient temperature 40°C (other on request)

Stainless steel cooling system, over temperature protected

Design

Compact Rittal TS cabinet; protection grade: IP54

Powder coated, RAL 7035

Mains supply below in cabinet

Cooling water connection in the plinth, 1/2" connections
(water pressure: 2-5 bar)

DC output bus bars:

- Low voltage outputs up to 50V on top of the cabinet
- Voltages above 50V: touch safe design


Mains power switch, fuses and sub distributor optional available in separate cabinet.

Moulded-case circuit breaker with short-circuit protection, low-voltage release and overload protection can be installed as option.

Dimensions (W x H x D) 800 x 2200 x 600mm incl. plinth

Values	Standard sizes - DC output ¹										other sizes on request			
	7200 A								6000 A		4000 A	3300 A	130 A	
DC current														
DC voltage	4 V	5 V	6 V	8 V	10 V	12 V	15 V	18 V	20 V	22 V	30 V	40 A	1000 V	
Mains supply	3 x 400V AC													
Weight	approx. 450 - 550 kg													

Standard dimensions



Cooling water connections are located in the plinth

Cooling water specification

For the water cooling system, city water with the following specifications should be used:

ph Value:	7,0 - 8,0 und TOC < 1,5 mg/l	Sulfate:	< 240 mg/l
Hardness:	<=1,3 mmol/l (<=7°dH)	Nitrate:	< 50 mg/l
Chloride:	<=100 mg/l	Sodium:	< 150 mg/l
Inlet temperature:	18-26°C	Water pressure:	> 2-5 bar

To operate this rectifier, and to keep the specified values of the cooling water, a closed cooling system is recommended.

The primary goal of these values is to eliminate internal condensation. Depending on the region and the environmental circumstances the units are operated it might become necessary to depart from above values!

Technical equipment, design and features: subject to change! For further information please contact plating electronic GmbH.

Control

Standard: peRB-interface

Optional: external control via analog signals, also with integrated isolation amplifier

Signals: 0-10V
0-1V
4-20mA
0-20mA (other on request)

Control unit pe280 for the controlling of DC power supplies of the series POWER STATION pe5710-W

Designed for electroplating applications
Large 3-line LCD-display,
polycarbonate-keypad for easy operation
Current and voltage infinitely adjustable
by UP / DOWN buttons



Current and voltage preset

Ampere-hour counter (totalizer)

Protection grade: IP54

Ambient temperature max. 40°C

Optional available functions

Preset counter, dosage counter *

Ramp function (start / stop ramp)

Timer function for ON / OFF *

Voltage / current alarm *

Operating hours counter

Chopper timer (pulse-capable rectifier type requested)

Pole changer function (mechanical / electronic) *

Programmable DC steps (14 individual steps) *

Extern ON

* Indication / alarm output

Control via: RS485, PROFIBUS, TCP/IP, PROFINET, Devicenet
(other on request)